

Table of Content

Page 1	TITLE PAGE
Page 2	CPU POWER
Page 3	CPU SIGNAL
Page 4	DDR3 MEMORY
Page 5	eMMC, SPI NOR FLASH
Page 6	SD CARD, SATA
Page 7	LVDS, HDMI
Page 8	CAMERA, EXP PORT
Page 9	EPDC EXP PORTS
Page 10	AUDIO
Page 11	USB
Page 12	ETHERNET
Page 13	JTAG, DEBUG
Page 14	SENSORS
Page 15	AUX SDIO CONN, CAN
Page 16	mPCIE CONN
Page 17	GPS MODULE
Page 18	BATTERY CHARGER
Page 19	PF0100 PMIC
Page 20	BOOT SELECT
Page 21	AUX VOLT REG
Page 22	COMM CHANNEL STEERING
Page 23	BUILD OPTION TABLES
Page 24	PIN MUX TABLE
Page 25	TEMPORARY DEVIATIONS

GENERAL DESIGN NOTES

1. Unless Otherwise Specified:
All resistors are in ohms, 5%, 1/16 Watt
All capacitors are in uF, 20%, 50V
All voltages are DC
All polarized capacitors are Tantalum
2. Critical compenents that require tolerances tighter than listed in Note 1are labeled with required tolerance on schematic. Non-critical components may be filled with tighter tolerance parts for BOM consolidation purposes, but may be changed to meet the general tolerances of Note 1 if desired.
3. Interrupted lines coded with the same letter or letter combinations are electrically connected.
4. Device type number is for reference only. The number varies with the manufacturer.
5. Special signal usage:
_B or 'n' Denotes - Active-Low Signal
<> or [] Denotes - Vectored Signals
6. Interpret diagram in accordance with American National Standards Institute specifications, current revision, with the exception of logic block symbology.


AC ADAPTER SPECIFICATIONS

DC Voltage Output: 5VDC
Current Output: ~ 5A (depending on application)
Polarity: 
Inner Diameter: 2.1mm
Outer Diameter: 5.5mm

i.MX6 SMART DEVICE SYSTEM

MCIMX6Q-SDB




Smart Device System Block Diagram



Revision History

Rev.	Code	Date	Description
X1		11/02/2011	Rev X1 Draft
A		12/15/2011	Release to Prototype Phase
AX1		02/09/12	Draft Rev B Respin: - Changed Audio CODEC to WM8962 per Marketing Request. - Removed two digital microphones. Changed mics to Wolfson WM2730 per Marketing. - Connected NVCC_TAG rail to GEN_3V3. - Added PFET Switch to SWBST supply to isolate it from System power. - Changed HDMI Media guard to CM020 IC to correct I2C HDMI issue. - Changed voltage sides on U9 level shifter. - Changed SW4 to 3.15V output. Moved audio 1.8V to GEN_1V8. - Changed camera IVS supply to VGEN2, other IVS loads moved to VGEN1. - Added isolation PFETs to Audio voltage supplies. - Switched USB_OTG_ID to pin ENET_RX_ER, USBOTG_OC to pin EIM2 and USBH1_OC to pin EIM_D30 to match pinmux functionality. - Added parallel termination resistors to PCIe differential clock traces. - Added next generation DEVSLP option for SATA connection. - Moved DISP0_PWR_EN to NANDF_WP_B to correct pull up voltage issue. - Deleted auxiliary 3.15V voltage regulator. - Designated several capacitors on processor core power rails as DNP. Validation proved unnecessary. - Moved I2C3 SDA from GPIO_16. This pin must be unconnected for Ethernet 1588 (time stamp) functionality to work. - Added shield ground pins to LVDS connectors. - Changed extrnal speaker capacitors to higher voltage rating. - Changed external regulator to supply 3.0V power to VSNVS. - Changed FF0100 microprocessor program circuit to DNP. - Added 5V supply to LCD expansion headers. - Connected HPOUTFB directly to Audio GND. - Connected VDDOTF to ground to boot PMIC from program settings. - Added isolation to prevent back powering board from USB when no battery present. - Back annotated Schematic to Layout. REFDES may have changed from Rev A. - Populated optional "PWRON" button circuit for use with Android. - Removed write protect on NOR Flash. - Removed LC filter circuit from external speakers. - Added an additional 2.100uF capacitors to MPCIE_3V3 next to connector. - Updated Power Rail, IOMUX, and Configuration Tables.
B		02/24/12	Release to Production - Depopulated following pull up/down resistors on VSNVS domain to reduce current requirements: R31, R108, R585 - Updated board per configuration table on Page 23
B2		05/04/12	Release to Production - Depopulated Q512 because of schematic error. - Cut trace to U12 pin 5 to prevent false USB plug in detects. - Added schematic page to detail applicable board TDAs that affect Rev B boards. - Populating CAN components U517 and U518 per Marketing Request. - Added resistor RX1 across pads for C515 to improve 24MHz clock stability. - Pull up resistors R629 and R639 have been changed to DNP. - Changed Marketing part number to MCIMX6Q-SDB - Changed R7 and R112 to DNP - Changed C540 to "POPULATED"
B3		05/25/12	- Changed DDR3 Memory to new 1.35V capable memory MT41K128M16JT. - Changed C540 to 1.0 uF per Wolfson recommendation. - Changed R183 and R189 to 2.37K pull ups to bring I2C rise time into specification.
B4		07/18/12	- Removed buffers U500 and U520 from digital microphone data outputs. - A note is added to show required hand wire modification. - The Battery Charge Done LED is disconnected and R522 is depopulated. - New parts RX2, CX1 and UX1 are added. Traces show required hand modifications. - Optional Power On Circuit has been disabled and U511 and R578 are now DNP. A new Diode DX1 has been added to allow EIM_D29 to sense a button press. - RESET button SW2 now connects to the PWRON pin of the PMIC. - Added 10K pull down resistor RX3 to SDCRE0 trace. - SIM Card Connector CON1 is now populated by default. - Changed resistors R174 and R176 and to depopulated by default. - LVDS0 EDID will not be connected to I2C2 channel unless needed.
B5		09/20/12	- Changed U1 to i.MX 6 T01.2 processor. - Changed C68 and C612 to DNP. - Populated C682 and C716 with 22uF capacitors.
C1		10/01/12	- All hand wire changes made in Revision B4 are now formally made in the netlist and the layout files. - Q512 is changed to populated. - Optional Start Up circuit has been modified. - PMIC Programming Micro-Processor is removed. - CX1 capacitor is changed to C504 - DX1 diode is changed to D4 - RX1 resistor changed to R216 - RX2 resistor changed to R19 - RX3 resistor changed to R635 - UX1 buffer changed to U507 - Add DNP Input to U13 buffer for USB_OTG_PWR_EN. - Buffer now powered from GEN_3V3. - FA_ANA and VDD_FA signals now connected to ground. - Added resistor options to EIM_DAY trace to EPD connector. - Connected EIM_DA9 to EPDC connector J508 to supply SDCE5 if needed. - Optional LDO U9 is now depopulated. - Added Connector J13 to support BT from SDIO Card through DNP resistors. - Added GPIO control of Battery Charge Enable pins through DNP resistor. - Changed C594 to 0.22uF - Changed C31 to 47uF. - Added C555 as second 22uF capacitor in parallel with C546. - Changed C561, C562, C586 and C596 to 0.47uF. - Added additional 47uF bulk capacitor C769 to SD2 socket VDD supply. - Added option to route HDMI DDC comms separate from I2C2 comms channel. - C597 populated to provide de-bounce to RESET circuit. - Depopulated C68, C612. Populated C682, C716 closer to pins. - Depopulated C39, C606, C607, C608, C609, C610, C673 and C681. - Added DNP R302 to provide alternate 5V supply path to USB_B1_VBUS. - Added DNP R632 to provide alternate gating of PMIC_5V source (tied to VDD80C). - Added DNP L25 and L26 to provide alternate 2.8V supply path to camera modules. - Added test pads to LVDS third data lanes to support testing with wall 24-bit panels. - Changed capacitors C6 and C7 to Zero Ohm resistors per PCIe Spec. - Changed Battery Charge ICs U502 and U503 to MAX8903C version.
C2		11/09/12	- Moved Ferrite Beads L10 and L17 to pads for L25 and L26. - Camera Analog Voltage supply moved to VGEN3. - Added notes for 24MHz crystal and USB layout design. - Changed R17, R21, R25, R27, R68, R85, R582, and R660 to 1% resistors due to lead time availability issues.
C3		02/20/13	- Changed BT500 Battery Holder to new manufacturer due to parts availability. - Changed R17, R21, R25, R27, R68, R85, R582, and R660 to 0.5% resistors due to parts availability. - Changed R97 and R106 pull up resistors to 4.7 Ohm. - Changed R19 pull up resistor to 10K Ohm.
C4		04/02/13	- DNP BH1, BH2 Standoffs. - Changed U8 part number to Programmed part MMPF0100F02ES - Changed R17, R21, R25, R27, R68, R85, R582, and R660 to 1% resistors due to lead time availability issues.
C5		02/16/15	- Updated Manufacturing numbers for U8, U512, U519
C6		02/02/16	- Updated Manufacturing numbers for U1, U8, U501, U521, J502, J503 - Changed title blocks to NXP


		Microcontroller Product Group 6501 William Cannon Drive West Austin, TX 78755-6598	
This document contains information proprietary to NXP and shall not be used for engineering design, procurement or manufacture in whole or in part without the express written permission of NXP Semiconductors.			
Designer: Mark Middleton	Drawing Title: MCIMX6Q-SMART DEVICE BOARD	ICAP Classification: GP:	IUC: PURB: X
Drawn by: Mark Middleton	Page Title: TITLE PAGE		
Approved: HW Platform Team	Size D	Document Number SCH-27516	PDF: SF-27516 Rev C6
Date: Tuesday, February 02, 2016		Sheet 1	of 25






The diagrams show three separate decoupling capacitor connections:

- VDDSQ_CAP:** A capacitor labeled C611 (DNP, 22UF) is connected between the VDDSQ supply rail and ground. A second capacitor labeled C612 (DNP, 22UF) is also connected between the VDDSQ supply rail and ground.
- VDDPU:** A capacitor labeled C68 (DNP, 22UF) is connected between the VDDPU supply rail and ground.
- VDDSNVS_CAP:** A capacitor labeled C54 (DNP) is connected between the VDDSNVS supply rail and ground.

NOTE:
In early designs of the Smart Device board, these bulk capacitors were used. After testing of the board, it was found that these capacitors could be removed with no effect. This reduces the capacitive loading on the internal processor LDOs. The components/footprints have been left in place in the event that future applications and/or software changes show that these capacitors are needed.





EIM_DA15	R217	0 DNP	COMP_INT	14
EIM_D16	R218	0 DNP	HDMI_DDC_DAT_IN	7,22
EIM_EB2	R219	0 DNP	HDMI DDC CLK IN	7,22




NOTE:
R302 is provided for testing with an alternate power supply for USB_H1_VBUS. It has not yet been tested. See the NXP HW User Guide for the Smart Device board for details (to be published 4Q12).







.....




4MB SPI NOR FLASH



NOTE:
RST_B pin is not enabled by default. It must be turned on by software. Therefore, part with RST_B pin can be used in existing designs that do not connect this pin.




SD CARD SOCKET



Layout:
50ohm, SD signals(SD_DATAx, SD_CMD, SD_CLK) length equal

SATA CONNECTOR


NOTE:
The new SATA specification retires the 3V3 pins as they were not being used by regular sized SATA devices. Pin 3 was repurposed to a device sleep functionality available in next generation SATA devices. Latest specification also recommends tying Pins 1 and 2 together, but leave floating.




Layout:

1. 100ohm diff pairs, length equal
2. Mount these capacitors very close to the connector J506.

hard drive standoff




LVDS



LVDS0

Place L515, L516, L517 and L518 CMCs close to J403 connector.




LVDS1

Layout: LVDS 100 ohm differential pairs

Place L511, L512, L513 and L514 CMCs close to J402 connector.

HDMI



Layout: HDMI 100 ohm differential pairs

NOTE:
When using HDMI, I2C2 bus is limited to 100 kHz to read EDID values due to HDMI standards. I2C2 bus speed should be limited to 100 kHz whenever Hot Plug Detect is high.


LVDS Connector notes:
Pin 1: This pin is the Display Enable pin. It is used to Enable/Disable the HannStar display.
Pin 5: This pin is the Display Brightness control. It provides a PWM signal to the display to increase/decrease display brightness depending on PWM duty cycle. This signal is shared by all displays, so all displays will change brightness together.



ICAP Classification: CP: IUO: PUBI: X			
Drawing Title: MCIMX6Q-SMART DEVICE BOARD			
Page Title: LVDS, HDMI			
Size C	Document Number SCH-27516 PDF: SPF-27516	Rev C6	
Date: Monday, February 01, 2016	Sheet 7	of 25	


CSI CMOS Sensor
OV5642 5M Pixel

Place R180 close to connector J9 to in the event
a reflected signal from camera needs to be suppressed.



Layout: 100 ohm differential pairs

MIPI DISPLAY
EXP PORT




MIPI Connector

NOTE:
The Camera Analog Power supply has been moved to VGEN3. NXP SW will program VGEN3
to operate at 2.8V. L25 and L26 are now populated and L10 and L17 are depopulated. See the
NXP HW User Guide for the Smart Device board for details (to be published 4Q12).

Place R158 and R159 near U15.
Acts as source termination.

MIPI CMOS Sensor
OV5640 5M Pixel




Layout: 100 ohm differential pairs





ICAP Classification: CP: IUO: PUBI: X			
Drawing Title: MCIMX6Q-SMART DEVICE BOARD			
Page Title: CAMERA, EXP PORT			
Size C	Document Number SCH-27516 PDF: SPF-27516	Rev C6	
Date: Monday, February 01, 2016	Sheet 8	of 25	

For MX60 EPD



Date:	Monday, February 01, 2016	Sheet	9	of	25
-------	---------------------------	-------	---	----	----






Power-on Strapping Pins

MODE2[3:0]


(Default assemle: 0000)
1100 BaseT, RMII1;
1101 BaseT, RMII2;
1110 100X, RGMII, 75OHMS;
1111 100X, TRANS, 75OHMS;
0000 BaseT, RGMII;
0001 BaseT, SGMII;
0010 1000X, RGMII, 50OHMS;
0011 1000X, RGMII, 75OHMS;
0100 1000X, TRANS, 50OHMS;
0101 1000X, TRANS, 75OHMS;
0110 100X, RGMII, 50OHMS;
0111 100X, TRANS, 50OHMS;
Others Reserved



ICAP Classification: CP: IUC: PUBI: X			
Drawing Title: MCIMX6Q-SMART DEVICE BOARD			
Page Title: ETHERNET			
Size C	Document Number SCH-27516 PDF: SPF-27516	Rev C6	
Date: Monday, February 01, 2016	Sheet 12 of 25		


DEBUG UART TO USB CONVERSION

Library Revision - A




Drivers located at:
<http://www.ftdichip.com/Products/ICs/FT232R.htm>

JTAG




ICAP Classification: CP: IUO: PUBI: X			
Drawing Title: MCIMX6Q-SMART DEVICE BOARD			
Page Title: JTAG, DEBUG			
Size C	Document Number SCH-27516 PDF: SPF-27516	Rev C6	
Date: Monday, February 01, 2016	Sheet 13 of 25		


Ambient Light Sensor





3-AXIS ACC



Barometer




Digital eCompass




AUX SDIO CARD SOCKET

BLUETOOTH CABLE CONNECTOR



Layout:
50ohm, SD signals(SD_DATAx, SD_CMD, SD_CLK) length equal




NOTE:
The AUX SDIO CARD SOCKET and the BLUETOOTH CABLE CONNECTOR have been designed and tested specifically for use with the WIFI/BT combo card SX-SDCAN-2830BT Developed and sold by Silex Technolgy. The developer may need to consult the datasheet of other WIFI solutions for compatibility with this card socket.

NOTE:
Pin 1 of the cable connector on the Smart Device board is opposite Pin 20 of the WIFI/BT module. For the FFC to lie flat, the pin order number needs to be reversed on the schematics.

NOTE:
J13 has been provided for testing the Bluetooth functionality of the SX-SDCAN-2830BT module. This part of the circuit has not yet been tested, which is why the initial boards are being shipped with isolation resistors R209 - R215 depopulated. Until fully tested, the developer assumes responsibility for enabling J13 tor testing purposed. See the NXP HW User Guide for the Smart Device board for details (to be published 4Q12).

OPTIONAL CAN PINOUT



ICAP Classification: CP: IUO: PUBI: X			
Drawing Title: MCIMX6Q-SMART DEVICE BOARD			
Page Title: AUX SDIO CONN, CAN			
Size C	Document Number SCH-27516 PDF: SPF-27516	Rev C6	
Date: Monday, February 01, 2016	Sheet 15 of 25		

Mini-PCIE





Place parallel termination resistors R6 and R8 as close to the mPCIe connector J1 as possible.

NOTE:
This design assumes a normal loading on the MPCIE_3V3 rail of up to 1A. PF0100 SW2 can supply a maximum of 2A current. If more than 1A loading is desired, the designer must consider other load on the GEN_3V3 rail and depopulate other loads to allow additional loading on the MPCIE_3V3 rail. The MPCIE_1V5 rail is allowed a maximum of 100 mA.



ICAP Classification:		CP: _____	IUO: _____	PUBI: <u>X</u>
Drawing Title:				
MCIMX6Q-SMART DEVICE BOARD				
Page Title:				
mPCIe CONN				
Size C	Document Number SCH-27516 PDF: SPF-27516			Rev C6
Date:	Monday, February 01, 2016	Sheet	16	of 25

GPS Receiver



ICAP Classification:		CP: <u> </u>	IUO: <u> </u>	PUBI: <u> X </u>
Drawing Title:				
MCIMX6Q-SMART DEVICE BOARD				
Page Title:				
GPS MODULE				
Size C	Document Number SCH-27516 PDF: SPF-27516			Rev C6
Date:	Monday, February 01, 2016	Sheet	17	of 25

External
Power
5 Vdc



Note:
Purpose for D502 is to provide voltage drop to lower
input voltage below 4.5V maximum voltage level
of PFUSE PMIC.

BATTERY 2 CHARGE CIRCUIT




NOTE:
Battery posts are meant for two, single cell 3.7 Li-ION batteries
to be added in parallel.

Note: Populate either
Option #1 for the Smart Device Board, or
Option #2 for the Smart Device Platform



ICAP Classification:		CP: _____	IUO: _____	PUBI: X _____
Drawing Title:				
MCIMX6Q-SMART DEVICE BOARD				
Page Title:				
BATTERY CHARGER				
Size C	Document Number SCH-27516 PDF: SPF-27516			F
Date:	Mondav, Februarv 01, 2016		Sheet 18 of 25	




Typical Power Requirements					
	Voltage	Power Up Sequence	Current Drawn (mA)	SYS 4V2 Current (mA)	NOTES
SW1A	1.375	1	2155	1001	
SW1B					
SW1C	1.375	2	1590	739	
SW2	3.3	5	653	728	
SW3A	1.5	3	1500	760	
SW3B					
SW4	3.15	6	200	213	
SWBST	5.0	13	300	507	
VGEN1	1.5	9	100	0	Supplied from SW4
VGEN2	1.5	10	250	0	Supplied from SW4
VGEN3	2.8	11	70	66	
VGEN4	1.8	12	310	189	
VGEN5	2.8	10	75	71	See Note on Page 20
VGEN6	3.3	8	160	178	
VSNVS	3.0	0	0.2	0	
VREFDDR	0.75	3	10	3	
Total System Current Requirements:				4454	

SYSTEM POWER RAILS					
Voltge	Rail Name	Block	Generated By	Current Capability (mA)	NOTES
5.0	PMIC_5V	USB	PF0100 SWBST	600	
		LVDS1			
		HDMI			
	AUX_5V	SATA	MAX8815	1000	
		LVDS0			
CAN					
3.3	GEN_3V3	EMMC	PF0100 SW2	2000	NVCC_LCD NVCC_EIM0/1/2 NVCC_GPIO NVCC_SD2/3 NVCC_NANDF NAND_JTAG
		SD3			
		NOR			
		SATA			
		LVDS			
		HDMI			
		MIPI			
		mPCIe			
		SENSORS			
	VGEN6_3V3	ETH	PF0100 VGEN6	200	
3.15	AUX_3V15	EXP HDR	PF0100 SW4	1000	Supplies: VGEN1 VGEN2
		TOUCH			
		GPS			
2.8	VDDHIGH_IN	IMX6	PF0100 VGEN5	100	
	VGEN3_2V5	CAMERA	PF0100 VGEN3	100	
2.5	GEN_2V5	SATA	IMX6 VDDHIGH_CAP	TBD	NVCC_MIPI
		HDMI			
		MIPI			
		mPCIe			
1.8	GEN_1V8	AUDIO	PF0100 VGEN4	350	NVCC_SD1 NVCC_CSI
		CAMERA			
		ACC			
1.5	VGEN2_1V5	CAMERA	PF0100VGEN2	250	
	VGEN1_1V5	GPS	PF0100 VGEN1	100	
		mPCIe			
	DDR_1V5	DDR	PF0100 SW3A/B	2500	
1.375	VDDCORE	ARMCORE	PF0100 SW1A/B	2500	
	VDDSOC	VDDSOC	PF0100 SW1C	1750	
0.75	VREFDDR	DDR	PF0100 VREFDDR	10	

Note:
To turn off board "AUTO ON" feature, depopulate R30 and R31, and populate U509. This feature has not yet been tested.

ICAP Classification: CP: IUO: PUBI: X				
Drawing Title: MCIMX6Q-SMART DEVICE BOARD				
Page Title: PF0100 PMIC				
Size C	Document Number SCH-27516 PDF: SPF-27516			Rev C6
Date:	Monday, February 01, 2016		Sheet 19 of 25	

Optional LDO




3.0V@ 300mA max

U9 is no longer required for PF0100 VSNVS issue, but may be desired for NVCC_PLL_VOUT.
It is being left in a depopulated condition. If the LDO is needed, R34 and R35 should be populated as follows:
For VSNVS (3.0V): R34 = 47K, R35 = 309K
For NVCC_PLL_OUT (1.1V): R34 = 47K, R35 = 82.5K


NOTE FOR VDDHIGH_IN LOADING ON VGEN5:
VDDHIGH was placed on VGEN5 early in the design as a compromise solution for a board designed primarily for software development. Validation of the i.MX6 processor has shown that operations at elevated temperatures may cause VDDHIGH_IN to require much more current than VGEN5 can supply. It is recommended for robust designs potentially operating at more extreme temperatures for VDDHIGH to be supplied from a power rail that can supply 250 mA or more. This allows for datasheet maximum of 125 mA for internal VDDHIGH_IN loads plus 125 mA for external PHY IO loads.

The optional LDO U9 shown on this page could be reconfigured to supply both VDDHIGH_IN and VDD_SNVS_IN loads to meet the additional current requirments

5.0V@1A DC2DC






ICAP Classification: CP: IUO: PUBI: X			
Drawing Title: MCIMX6Q-SMART DEVICE BOARD			
Page Title: AUX VOLT REG			
Size C	Document Number SCH-27516 PDF: SPF-27516	Rev C6	
Date: Monday, February 01, 2016	Sheet 20 of 25		




NOTE:
On Rev B4 and later designs, the RESET button is connected directly to the PWRON input of the PMIC. This will cause a complete board reset (Processor & PMIC) when the RESET button is pressed.

U/I KEY




Boot Configuration Select



NOTE:
Place series resistors so as to minimize EIM portion of trace length. Two layout possibilities include:
1) As close to processor as possible.
2) Close to other componets using EIM signals.

Boot Select Table

8	7	6	5	4	3	2	1
BT_CFG1_7	BT_CFG1_6	BT_CFG1_5	BT_CFG1_4	BT_CFG2_6	BT_CFG2_5	BT_CFG2_4	BT_CFG2_3
011X = MMC/eMMC Boot				X0 = 1-bit X1 = 4-bit 10 = 8-bit	01 = SD2 Boot 10 = SD3 Boot 11 = SD4 Boot		
010X = SD/eSD Boot				X0 = 1-bit X1 = 4-bit	01 = SD2 Boot 10 = SD3 Boot 11 = SD4 Boot		
0010 = SATA Boot				X	X	X	0





BOOT MODES:
00 Boot from fuses
01 Serial downloader
10 Boot from board settings
11 Reserved





ICAP Classification: CP: IUC: PUBI: X			
Drawing Title: MCIMX6Q-SMART DEVICE BOARD			
Page Title: BOOT SELECT			
Size C	Document Number SCH-27516 PDF: SPF-27516	Rev C6	
Date: Monday, February 01, 2016	Sheet 21 of 25		

I2C1





NOTE:
R183 and R189 were changed to bring I2C rise time from LOW >> HIGH within electric specification. If using a CODEC other than the one used in this design, it may be possible to switch pull up resistors back to 4.7K.

I2C2



I2C3



CSP11



NOTE:
On all three pad resistor options, resistors are to be initially populated on pads 1 - 2 (Option A). Users may move resistors from their default locations as needed.



ICAP Classification: CP: IUO: PUBI: X			
Drawing Title: MCIMX6Q-SMART DEVICE BOARD			
Page Title: COMM CHANNEL STEERING			
Size C	Document Number SCH-27516 PDF: SPF-27516	Rev C6	
Date: Monday, February 01, 2016	Sheet 22 of 25		

Build Option: MCIMX6Q-SDB

1.	CAN Output not populated: J10
2.	Battery Charging circuit not populated: C507, C508, C510, C511, C512, C513, C514, C515, C517, C518, C520, C521, C526, C527, C528, C529, CON2, CON3, L502, L503, R512, R513, R514, R515, R516, R518, R519, R527, R528, R530, R531, R532, R533, R534, R535, R536, R537, R538, R539, R542, R565, R577, R729, RT500, RT501, U502, U503
3.	SPI NOR Flash not populated: C83, R149, R643, R646, U14
4.	MIPI Display/Camera Expansion Ports not populated: C28, C29, C30, C50, C116, C117, C123, C124, C585, C587, C588, C602, J11, J5, L25, R26, R165, R173, R175, R726, U10
5.	Audio Block Components not populated: C1, C128, C558, R569, R573, U501, U510, U521
6.	EPDC Port Connector not populated: J508
7.	Ambient Light Sensor not populated: C108, R184, R185, R188, R190, R191, U17
8.	GPS Module not populated: C115, C118, C764, C765, J12, L22, L23, Q516, Q517, Q518, Q519, R186, R192, R194, R664, R668, R669, R671, R672, R673, U19
9.	Extra Bulk Capacitors not populated: C39, C54, C68, C606, C607, C608, C609, C610, C611, C612, C673, C681
10.	BlueTooth Connector Isolation Resistors: R209, R210, R211, R212, R213, R214, R215

Build Option: MCIMX6Q-SDP MCIMX6DL-SDP

1.	CAN Output not populated: J10
2.	OverVoltage Protection circuit not populated: (OverVoltage Protection provided by battery charge ICs) D5, D500, D501, D502, D503, J501, Q1, Q6, Q503, R1, R2, R3, R303, R500, R505, R520, R524, SW3
3.	Extra Bulk Capacitors not populated: C39, C54, C68, C606, C607, C608, C609, C610, C611, C612, C673, C681
4.	BlueTooth Connector Isolation Resistors: R209, R210, R211, R212, R213, R214, R215



PIN MUX TABLES

Ball Name	Ball Number	IO MUX	Use
CSIO_DAT10	M1	ALT3	UART1_TXD_MUX
CSIO_DAT11	M3	ALT3	UART1_RXD_MUX
CSIO_DAT12	M2	ALT0	CSIO_D[12]
CSIO_DAT13	L1	ALT0	CSIO_D[13]
CSIO_DAT14	M4	ALT0	CSIO_D[14]
CSIO_DAT15	M3	ALT0	CSIO_D[15]
CSIO_DAT16	L4	ALT0	CSIO_D[16]
CSIO_DAT17	L3	ALT0	CSIO_D[17]
CSIO_DAT18	M6	ALT0	CSIO_D[18]
CSIO_DAT19	L6	ALT0	CSIO_D[19]
CSIO_DATA	N1	ALT4	AUD3_TXC
CSIO_DAT3	P2	ALT4	AUD3_TXD
CSIO_DATA6	N4	ALT4	AUD3_TXF5
CSIO_DATA7	N3	ALT4	AUD3_RXD
CSIO_DATA8	N6	ALT4	I2C1_SDA
CSIO_DATA9	N3	ALT4	I2C2_SCL
CSIO_MCLK	P4	ALT0	CSIO_HSYNC
CSIO_PIXCLK	P1	ALT0	CSIO_PIXCLK
CSIO_VSYNC	N2	ALT0	CSIO_VSYNC
DIO_DISP_CLK	N19	ALT1	DIO_DISP_CLK
DIO_PIN13	N21	ALT1	DISPO_DRDT
DIO_PIN2	N23	ALT1	DISPO_HSYNCH
DIO_PIN3	N20	ALT1	DISPO_VSYNCH
DIO_PIN4	P23	ALT1	DISPO_CONTRST
DISPO_DATA0	P24	ALT1	DISPO_DATA[0]
DISPO_DATA1	P22	ALT1	DISPO_DATA[1]
DISPO_DATA10	R21	ALT1	DISPO_DATA[10]
DISPO_DATA11	T23	ALT1	DISPO_DATA[11]
DISPO_DATA12	T24	ALT1	DISPO_DATA[12]
DISPO_DATA13	R20	ALT1	DISPO_DATA[13]
DISPO_DATA14	U23	ALT1	DISPO_DATA[14]
DISPO_DATA15	T22	ALT1	DISPO_DATA[15]
DISPO_DATA16	T21	ALT1	DISPO_DATA[16]
DISPO_DATA17	U24	ALT1	DISPO_DATA[17]
DISPO_DATA18	V23	ALT1	DISPO_DATA[18]
DISPO_DATA19	U23	ALT1	DISPO_DATA[19]
DISPO_DATA2	P23	ALT1	DISPO_DATA[2]
DISPO_DATA20	U22	ALT1	DISPO_DATA[20]
DISPO_DATA21	T20	ALT1	DISPO_DATA[21]
DISPO_DATA22	V24	ALT1	DISPO_DATA[22]
DISPO_DATA23	W24	ALT1	DISPO_DATA[23]
DISPO_DATA3	P21	ALT1	DISPO_DATA[3]
DISPO_DATA4	P20	ALT1	DISPO_DATA[4]
DISPO_DATA5	R23	ALT1	DISPO_DATA[5]
DISPO_DATA6	R23	ALT1	DISPO_DATA[6]
DISPO_DATA7	R24	ALT1	DISPO_DATA[7]
DISPO_DATA8	R22	ALT1	DISPO_DATA[8]
DISPO_DATA9	T25	ALT1	DISPO_DATA[9]
EIM_D21	H20	ALT4	USB_OTG_OC
EIM_D22	E23	ALT4	USB_OTG_PWR_EN
EIM_D24	F22	ALT2	UART3_TXD_MUX
EIM_D25	G22	ALT2	UART3_RXD_MUX
EIM_D30	J20	ALT6	USB_H1_OC
ENET_MDC	V20	ALT1	MDC
ENET_MDIO	V23	ALT1	MDIO
ENET_REF_CLK	V22	ALT1	ENET_TX_CLK
ENET_RX_ER	W23	ALT0	USB_OTG_ID
GPIO_0	T3	ALT0	CLKO
GPIO_1	T4	ALT1	WDOG_B
GPIO_3	R7	ALT2	I2C3_SCL
GPIO_6	T3	ALT3	I2C3_SDA
GPIO_7	R3	ALT3	TXCAN
GPIO_8	R5	ALT3	RXCAN
GPIO_16	R2	ALT1	No-Connect
KEY_COL0	W3	ALT0	SCLK
KEY_COL1	U7	ALT0	MISO
KEY_COL3	U3	ALT4	I2C2_SCL
KEY_ROW0	V6	ALT0	CSPI1_MOSI
KEY_ROW1	U6	ALT0	CSPI1_SS0
KEY_ROW3	T7	ALT4	I2C2_SDA
KEY_ROW2	W4	ALT6	HDMI_CEC_IN

Ball Name	Ball Number	IO MUX	Use
NANDF_D4	A19	ALT1	SD2_DATA4
NANDF_D5	B18	ALT1	SD2_DATA3
NANDF_D6	E17	ALT1	SD2_DATA6
NANDF_D7	C18	ALT1	SD2_DATA7
RGMII_RDO	C24	ALT1	RGMII_RDO
RGMII_RD1	B23	ALT1	RGMII_RD1
RGMII_RD2	B24	ALT1	RGMII_RD2
RGMII_RD3	D23	ALT1	RGMII_RD3
RGMII_RX_CTL	D22	ALT1	RGMII_RX_CTL
RGMII_RXC	B23	ALT1	RGMII_RXC
RGMII_TD0	C22	ALT1	RGMII_TD0
RGMII_TD1	F20	ALT1	RGMII_TD1
RGMII_TD2	E21	ALT1	RGMII_TD2
RGMII_TD3	A24	ALT1	RGMII_TD3
RGMII_TX_CTL	C23	ALT1	RGMII_TX_CTL
RGMII_TXC	D21	ALT1	RGMII_TXC
SD1_DATA3	F18	ALT3	PWM0
SD2_CLK	C21	ALT0	SD2_CLK
SD2_CMD	F19	ALT0	SD2_CMD
SD2_DATA0	A22	ALT0	SD2_DATA0
SD2_DATA1	E20	ALT0	SD2_DATA1
SD2_DATA2	A23	ALT0	SD2_DATA2
SD2_DATA3	B22	ALT0	SD2_DATA3
SD3_CLK	D14	ALT0	SD3_CLK
SD3_CMD	B13	ALT0	SD3_CMD
SD3_DATA0	E14	ALT0	SD3_DATA0
SD3_DATA1	F14	ALT0	SD3_DATA1
SD3_DATA2	A15	ALT0	SD3_DATA2
SD3_DATA3	B15	ALT0	SD3_DATA3
SD3_DATA4	D13	ALT0	SD3_DATA4
SD3_DATA5	C13	ALT0	SD3_DATA5
SD3_DATA6	E13	ALT0	SD3_DATA6
SD3_DATA7	F13	ALT0	SD3_DATA7
SD4_CLK	E16	ALT0	SD4_CLK
SD4_CMD	B17	ALT0	SD4_CMD
SD4_DATA0	D18	ALT1	SD4_DATA0
SD4_DATA1	B19	ALT1	SD4_DATA1
SD4_DATA2	F17	ALT1	SD4_DATA2
SD4_DATA3	A20	ALT1	SD4_DATA3
SD4_DATA4	E18	ALT1	SD4_DATA4
SD4_DATA5	C19	ALT1	SD4_DATA5
SD4_DATA6	B20	ALT1	SD4_DATA6
SD4_DATA7	D19	ALT1	SD4_DATA7

Reserved For i.MX6DLS			
NANDF_WP_B	E15	ALT3	DISPO_WR
EIM_RW	K20	ALT8	EPDC_SDDO7
EIM_LBA	K22	ALT8	EPDC_SDDO4
EIM_CS0	H24	ALT8	EPDC_SDDO6
EIM_EB1	K23	ALT8	EPDC_SDSHR
EIM_EB2	E22	ALT8	EPDC_SDDO5
EIM_A16	H23	ALT8	EPDC_SDDO0
EIM_A18	J22	ALT8	EPDC_PWRCTRL0
EIM_A21	H23	ALT8	EPDC_GDCLK
EIM_A22	F24	ALT8	EPDC_GDGP
EIM_A23	J21	ALT8	EPDC_GDOE
EIM_A24	F25	ALT8	EPDC_GDRL
EIM_D17	F21	ALT8	EPDC_VCOM0
EIM_D27	E25	ALT8	EPDC_SDOE
EIM_D31	H21	ALT8	EPDC_SDCCLK
EIM_DA1	J23	ALT8	EPDC_SOLE
EIM_DA2	L21	ALT8	EPDC_BDR0
EIM_DA3	K24	ALT8	EPDC_BDR1
EIM_DA4	L22	ALT8	EPDC_SDCB0
EIM_DA5	L23	ALT8	EPDC_SDCB1
EIM_DA6	K25	ALT9	EPDC_SDCB2
EIM_DA10	M22	ALT8	EPDC_SDDO1
EIM_DA11	M20	ALT8	EPDC_SDDO3
EIM_DA12	M24	ALT8	EPDC_SDDO2

Ball Name	Ball Number	IO MUX	Use	GPIO Function	Direction	Active
SD1_CMD	B21	ALT3	GPIO1[18]	ACCL_INT_IN	Input	High
EIM_DA9	M21	ALT3	GPIO3[9]	ALS_INT	Input	High
NANDF_WP_B	E15	ALT3	GPIO6[9]	DISPO_WR	Output	High
NANDF_RB0	B16	ALT3	GPIO6[10]	AUX_5V_EN	Output	High
EIM_DA15	N24	ALT3	GPIO3[15]	BARO_INT	Input	High
NANDF_CS2	A17	ALT3	GPIO6[15]	CABC_EN0	Output	High
NANDF_CS3	D16	ALT3	GPIO6[16]	CABC_EN1	Output	High
GPIO_19	P5	ALT3	GPIO4[3]	CAN1_STBY	Output	High
NANDF_ALE	A16	ALT3	GPIO6[8]	CAP_TCH_INT0	Input	High
NANDF_CLE	C15	ALT3	GPIO6[7]	CAP_TCH_INT1	Input	High
EIM_A25	H19	ALT3	GPIO5[2]	CHG_FLT1_B	Input	Low
EIM_DA14	N23	ALT3	GPIO3[14]	CHG_FLT2_B	Input	Low
EIM_D23	D25	ALT3	GPIO3[23]	CHG_STATUS1_B	Input	Low
EIM_DA13	M23	ALT3	GPIO3[13]	CHG_STATUS2_B	Input	Low
KEY_COL2	W6	ALT3	GPIO4[10]	CODEC_PWR_EN	Output	High
EIM_D16	C25	ALT3	GPIO3[16]	COMP_INT	Input	High
SD1_DATA2	E19	ALT3	GPIO1[19]	CSI_PWIN	Output	High
SD1_CLK	D20	ALT3	GPIO1[20]	CSI_RST_B	Output	High
SD1_DATA0	A21	ALT3	GPIO1[16]	CSIO_PWIN	Output	High
SD1_DATA1	C20	ALT3	GPIO1[17]	CSIO_RST_B	Output	High
EIM_WAIT	M25	ALT3	GPIO3[0]	DIO_D0_CS	Output	High
EIM_BCLK	N22	ALT3	GPIO6[31]	DIO_D1_CS	Output	High
NANDF_CS1	C16	ALT3	GPIO6[14]	DISPO_PWR_EN	Output	High
EIM_D28	G23	ALT3	GPIO3[28]	DISPO_RD	Output	High
EIM_DA8	L24	ALT3	GPIO3[8]	DISPO_RST_B	Output	Low
NANDF_CS0	F13	ALT3	GPIO6[11]	DISPO_RST_B	Output	Low
EIM_CS1	J23	ALT3	GPIO2[24]	DOK_B	Input	Low
EIM_A17	G24	ALT3	GPIO2[21]	E_PMIC_GOOD_B	Input	Low
EIM_D20	G20	ALT3	GPIO3[20]	EPDC_PMIC_WAKEUP	Output	High
EIM_A19	G25	ALT3	GPIO2[19]	EPDC_PWRCTRL1	Output	High
EIM_A20	H22	ALT3	GPIO2[18]	EPDC_PWRCTRL2	Output	High
EIM_OE	J24	ALT3	GPIO2[25]	EPDC_PWRIRQ	Input	High
ENET_TX_EN	V21	ALT3	GPIO1[28]	ETH_WOL_INT	Input	High
EIM_D18	D24	ALT3	GPIO3[18]	GPS_PPS	Input	High
EIM_DAO	L20	ALT3	GPIO3[0]	GPS_PWREN	Output	High
EIM_EB0	K21	ALT3	GPIO2[28]	GPS_RESET_B	Output	Low
SD3_RST	D15	ALT3	GPIO7[8]	HEADPHONE_DET	Input	Low
GPIO_3	R4	ALT3	GPIO1[3]	KEY_VOL_DN	Input	Low
GPIO_4	R6	ALT3	GPIO1[4]	KEY_VOL_UP	Input	Low
KEY_COL4	T6	ALT3	GPIO4[14]	PCI_E_DIS_B	Output	Low
GPIO_17	R1	ALT3	GPIO7[12]	PCI_E_RST_B	Output	Low
EIM_D19	G21	ALT3	GPIO3[19]	PCI_E_PWR_EN	Output	High
GPIO_18	P6	ALT3	GPIO7[13]	PMIC_INT_B	Input	Low
EIM_D29	J19	ALT3	GPIO3[29]	PWR_BTN_SNS	Input	High
ENET_CR5_DV	U21	ALT3	GPIO1[25]	RGMII_Nrst	Output	High
NANDF_D2	F16	ALT3	GPIO2[2]	SD2_CD_B	Input	Low
NANDF_D3	D17	ALT3	GPIO2[3]	SD2_WP	Input	High
NANDF_D0	A18	ALT3	GPIO2[0]	SD3_CD_B	Input	Low
NANDF_D1	C17	ALT3	GPIO2[1]	SD3_WP	Input	High
EIM_EB3	F23	ALT3	GPIO2[31]	SENSOR_PWR_EN	Output	High
EIM_DA7	L23	ALT3	GPIO3[7]	KP_LOCK	Input	High
EIM_D26	E24	ALT3	GPIO3[26]	TS_INT	Input	High
ENET_RXD0	W21	ALT3	GPIO1[27]	UOK_B	Input	Low
ENET_RXD1	W22	ALT3	GPIO1[26]	RGMII_INT	Input	High
ENET_TXD0	U20	ALT3	GPIO1[30]	DISPO_WR	Output	High
ENET_TXD1	W20	ALT3	GPIO1[29]	USB_H1_PWR_EN	Output	High
GPIO_2	T1	ALT3	GPIO1[2]	USR_DEF_RED_LED	Output	High
GPIO_9	T2	ALT6	GPIO1[9]	MICROPHONE_DET	Input	Low
KEY_ROW4	V3	ALT3	GPIO4[15]	SATA_DEVSLP	Output	High
CSIO_DATA_EN	P3	ALT3	GPIO5[20]	PCI_E_WAKE_B	Input	Low

I2C1 Bus (1.8V)

Peripheral	Bus Activity Level	Speed (kbps)	Addresses (hex)	Default Address (hex)
CSI Bus Camera	Low	400	Write: 0x78	Write: 0x78
Auido CODEC	Low	400	0x34, 0x36	0x34
MMA 8451Q Accelerometer	Low	400	0x3A, 0x39	0x39
I2C1_SDA = CSIO_DAT8 I2C1_SCL = CSIO_DATA9				

I2C2 Bus (3.3V)

Peripheral	Bus Activity Level	Speed (kbps)	Addresses (hex)	Default Address (hex)
PF0100 PMIC	Low	400	0x08 - 0x0F	0x08
MIPI Bus Camera	Low	400	0x3C	0x3C
MIPI Bus Display	TBD	TBD	TBD	TBD
HDMI EDID	Low	100	0x50	0x50
LVDS0 EDID	Low	100	0x50	0x50
LVDS0 TOUCH SCREEN	High	400	0x82	0x82
RGB TFT LCD DISPLAY	TBD	TBD	TBD	TBD
LCD TOUCH SCREEN	Low	400	0x68, 0x69, 0x6A, 0x6B	0x68
I2C2_SDA = KEY_ROW3 I2C2_SCL = KEY_COL3				

I2C3 Bus (3.3V)

Peripheral	Bus Activity Level	Speed (kbps)	Addresses (hex)	Default Address (hex)
LVDS1 EDID	Low	100	0x50	0x50
LVDS1 TOUCH SCREEN	High	400	0x82	0x82
PCIe EXP PORT	TBD	TBD	TBD	TBD
EPDC DISPLAY CARD	Low	400	0x68, 0x69, 0x6A, 0x6B	0x68
AMBIENT LIGHT SENSOR	Low	400	0x44	0x44
DIGITAL eCOMPASS	Low	400	0x0E	0x0E
BAROMETER	Low	400	0x60	0x60
I2C3_SDA = GPIO_16 I2C3_SCL = GPIO_3				



HISTORY OF TEMPORARY DEVIATIONS

TDA 4100

1. Digital microphone ANALOG DEVICES ADMP421 was used in place of WOLFSON WM7230 due to supply shortage. Affects U500 and U520.

TDA 4112

Replaced TDA 4100

1. Digital microphone ANALOG DEVICES ADMP421 was used in place of WOLFSON WM7230 due to supply shortage. Affects U500 and U520.
2. Q512 was depopulated due to schematic mistake. Removes battery charge from USB option.
3. Depopulate R30 on MCIMX6DL-SD boards only.
i.MX6DL Processor configured for Smart PMIC mode. Not compatible with board design. Removes SW ability to shutdown the board.

TDA 4136

1. Solder a 0402 2.2M Ohm resistor across pins of C55. Some i.MX6Q Processors require this resistor to stabilize the 24MHz crystal circuit, in order to start up within the required time interval.

TDA 4221 (6DL) / TDA 4222 (6Q)

1. Schematic revision B3 changed DDR3 memory to MT41K128M16JT-125-K. Due to unavailability of new part, this TDA authorizes the continued use of MT41J128M16HA-15.
2. Change C540 to 1.0uF capacitor.
3. Change resistors R183 and R189 to 2.37K Ohm resistors.

TDA 4275

1. Remove buffers U500 and U520 from digital Microphone data signal. Replace with hand wire mod.
2. Add WDOG_B reset capability (UX1, RX2, CX1).
3. Add diode DX1 to EIM_D19 to allow GPIO sense of power button press.
4. Change RESET button press to connect to PMIC PWRON pin. RESET press now causes global reset.
5. Add 10K pull down resistor RX3 to SDCKE0 pin.
6. Depopulate Resistors R174 and R176 to disconnect LVDS0 EDID from I2C2 communications channel.
7. Populate Battery Connector Header CON3.
8. Populate SIM Card Connector CON1.
9. Remove U1 from BOM (in preparation for next revision MX 6 silicon).
10. On MCIMX6DL-SDP boards, populate resistor R30 with 1K Ohm resistor.

TDA 4425

1. Depopulate ferrite beads L10 and L17.
2. Populate ferrite beads L25 and L26 (wih Murata BLM18PG121SH1).

TDA 4502

1. Change R17, R21, R25, R27, R68, R85, R582, and R660 to 0.5% resistors due to parts availability.

TDA 4516

1. Change R17, R21, R25, R27, R68, R85, R582, and R660 to 1.0% resistors due to parts availability.

TDA 4538

1. U8 PMIC was installed without F0 programming (U8 not stamped F0). TDA is to program part in place.

CHANGE REVISION DEFECT TRACKING

REV:	Change:	Reference Defect Number:
B4	Removed buffers U500 and U520 from digital microphone data outputs.	ENGR00181056 ENGR00211969
B4	The Battery Charge Done LED is disconnected and R522 is depopulated. New parts RX2, CX1 and UX1 are added. Traces show required hand modifications.	ENGR00211943
B4	Optional Power On Circuit has been disabled and U511 and R578 are now DNP. A new Diode DX1 has been added to allow EIM_D29 to sense a button	ENGR00181039 ENGR00211948
B4	RESET button SW2 now connects to The PWRON pin of The PMIC.	ENGR00211979
B4	Added 10K pull down resistor RX3 to SDCKE0 trace.	ENGR00211962
B4	SIM Card Connector CON1 is now populated by default.	ENGR00224087
B4	Battery Connector Header CON3 is now populated by default.	ENGR00224089
B4	Changed resistors R174 and R176 and to depopulated by default. LVDS0 EDID will not be connected to I2C2 channel unless needed.	ENGR00211965
B4	Replaced digital microphones with Analog Devices ADMP421.	ENGR00211964
B4	Disabled USR_DEF_GRN_LED circuit. Configured GPIO_1 for WDOG_B output.	ENGR00211973
C	Q512 is Changed to populated.	ENGR00211943
C	Optional Start Up Circuit has been modified.	ENGR00181039
C	PMIC Programming Micro-Processor is removed.	ENGR00224090
C	Add DNP Input to U13 buffer for USB_OTG_PWR_EN. Buffer now powered from GEN_3V3.	ENGR00319341
C	FA_ANA and VDD_FA signals now connected to ground.	ENGR00213511
C	Added resistor options to EIM_DA7 trace to EPD connector.	ENGR00181054 ENGR00211953
C	Connected EIM_DA9 to EPDC Connector J508 to supply SDCE5 if needed.	ENGR00213510
C	Optional LDO U9 is now depopulated.	ENGR00224091
C	Added Connector J13 to support BT from SDIO Card. Connector is isolated by DNP resistors on Rev C boards.	ENGR00181035 ENGR00211946
C	Added GPIO control of Battery Charge Enable pins.	ENGR00217643
C	Changed C594 to 0.22uF, changed C31 to 47uF, added C555 as second 22uF capacitor in parallel with C546, changed C561, C562, C586 and C596 to 0.47uF. Changes made per recommendation of MMPF0100NPEP team.	ENGR00224093
C	Added additional 47uF bulk capacitor C769 to SD2 socket VDD supply.	ENGR00224094
C	Added option to route HDMI DDC comms separate from I2C2 comms channel.	ENGR00215026
C	C597 populated to provide de-bounce to RESET circuit.	ENGR00224095
C	Depopulated C68, C612. Populated C682, C716 closer to pins.	ENGR00224096
C	Depopulated C39, C606, C607, C608, C609, C610, C673 and C681.	ENGR00224097
C	Added DNP R302 to provide alternate 5V supply path to USB_H1_VBUS.	ENGR00224098
C	Added DNP R632 to provide alternate gating of PMIC_5V source (tied to VDDSOC).	ENGR00224098
C	Added DNP L25 and L26 to provide alternate 2.8V supply path to camera modules.	ENGR00224099
C	Added TP31, TP32, TP509, and TP510 to bring out third data lane for both LVDS0 and LVDS1.	ENGR00214325 ENGR00214502
C	Change blocking capacitors C6 and C7 to Zero Ohm resistors R307 and R308. PCIe specification requires blocking capacitors to be on transmit side of	ENGR00226040
C2	Depopulate L10 and L17. Move Ferrite beads to L25 and L26	ENGR00231769
C3	Changed R97 and R106 pull up resistors to 4.7K to reduce current on VSNVS	ENGR00237171
C3	Changed R19 to 10K pull up resistor to prevent WDOG reset during POR.	ENGR00234394
C3	Added note to BlueTooth connector that RXD and TXD traces are crossed.	ENGR00239363



ICAP Classification:		CP: _____	IUO: _____	PUBI: <u>X</u>
Drawing Title:				
MCIMX6Q-SMART DEVICE BOARD				
Page Title:				
TEMPORARY DEVIATIONS				
Size C	Document Number SCH-27516 PDF: SPF-27516			Rev C6
Date:	Monday, February 01, 2016		Sheet	25 of 25